

# MV-CH210-90YM/YC

21 MP CMOS CoaXPress Area Scan Camera



GEN<i>i</i>CAM


## Introduction

MV-CH210-90YM/YC camera adopts Gsprint 4521 sensor to provide high-quality image. It uses CXP-12 interface to transmit non-compressed images in real time, and its max. frame rate can reach 222 fps in full resolution.

## Key Feature

- Resolution of 5120 × 4096, pixel size of 4.5 μm × 4.5 μm.
- Adopts global shutter CMOS to provide high dynamic range, SNR, and high-quality images.
- Supports LSC sequencer polling function.
- Low power consumption without fans.
- Adopts CXP-12 interface to transmit data.
- Compatible with CoaXPress Protocol and GenICam Standard.

## Dimension




## Available Model

- Mono camera: MV-CH210-90YM-M58S-NN
- Color camera: MV-CH210-90YC-M58S-NN

## Applicable Industry

Electronics, semiconductor, PCB AOI, 3D application, motion capture, etc.

## Sensor Quantum Efficiency



# Specification

Model	MV-CH210-90YM	MV-CH210-90YC
<b>Camera</b>		
Sensor type	CMOS, global shutter	
Sensor model	Gpixel Gsprint 4521	
Pixel size	4.5 $\mu\text{m}$ $\times$ 4.5 $\mu\text{m}$	
Sensor size	23.04 mm $\times$ 18.43 mm	
Resolution	5120 $\times$ 4096	
Max. frame rate	222 fps @5120 $\times$ 4096 Mono 8	222 @5120 $\times$ 4096 Bayer GB 8
Dynamic range	65 dB	
SNR	43 dB	
Gain	Supports 1.0 $\times$ , 2.0 $\times$ , 4.0 $\times$	
Exposure time	4 $\mu\text{s}$ to 10 sec	
Exposure mode	Off/Once/Continuous exposure mode	
Mono/color	Mono	Color
Pixel format	Mono 8/10/12	Bayer GB 8/10/12
Binning	Supports 1 $\times$ 1, 1 $\times$ 2, 1 $\times$ 4, 2 $\times$ 1, 2 $\times$ 2, 2 $\times$ 4, 4 $\times$ 1, 4 $\times$ 2, 4 $\times$ 4	
Decimation	Supports 1 $\times$ 1, 1 $\times$ 2, 1 $\times$ 4, 2 $\times$ 1, 2 $\times$ 2, 2 $\times$ 4, 4 $\times$ 1, 4 $\times$ 2, 4 $\times$ 4	
Reverse image	Supports horizontal and vertical reverse image output	
<b>Electrical features</b>		
Data interface	CoaXPress with Micro-BNC interface	
Digital I/O	12-pin P10 connector provides power and I/O, including opto-isolated input $\times$ 1 (Line 0), opto-isolated output $\times$ 1 (Line 1), bi-directional non-isolated I/O $\times$ 1 (Line 2), and RS-232 $\times$ 1.	
Power supply	12 VDC to 24 VDC, CXP-0 and CXP-1 connectors support PoCXP	
Power consumption	Typ. 18 W@24 VDC	Typ. 16.3 W@24 VDC
<b>Mechanical</b>		
Lens mount	M58*0.75, optical back focal length 11.48 mm (0.5")	
Dimension	84 mm $\times$ 84 mm $\times$ 62.5 mm (3.3" $\times$ 3.3" $\times$ 2.5")	
Weight	Approx. 650 g (1.4 lb.)	
Ingress protection	IP40 (under proper lens installation and wiring)	
Temperature	Working temperature: 0 $^{\circ}\text{C}$ to 50 $^{\circ}\text{C}$ (32 $^{\circ}\text{F}$ to 122 $^{\circ}\text{F}$ ) Storage temperature: -30 $^{\circ}\text{C}$ to 70 $^{\circ}\text{C}$ (-22 $^{\circ}\text{F}$ to 158 $^{\circ}\text{F}$ )	
Humidity	20% to 95% RH, non-condensing	
<b>General</b>		
Client software	MVS or frame grabber software meeting with CoaXPress Protocol	
Operating system	32/64-bit Windows 7/10	
Compatibility	CoaXPress, GenICam	
Certification	CE, RoHS, KC	

**HIKROBOT**

Hangzhou Hikrobot Co., Ltd.  
en.hikrobotics.com

© Hangzhou Hikrobot Co., Ltd. All Rights Reserved.

Hangzhou Hikrobot does not tolerate any infringement. Any organization or individual may not imitate or reproduce in whole or in part of the content. The data herein is based on Hikrobot's internal evaluation. Actual data may vary depending on specific configuration and operating condition. The information herein is subject to change without notice. All the content has been checked conscientiously. Nevertheless, Hikrobot shall not be liable to damages resulting from errors, inconsistencies or omissions.